5mb al

1. A tracheal cannula for insertion into the trachea following a tracheotomy, having a shaft and a cuff for blocking the tracheal cross-sectional area surrounding the shaft, characterized such that in the section of the shaft lying above the cuff a window is constructed such that this is covered by an air-permeable membrane.

- Tracheal cancula based on claim 1, characterized such that the
  membrane is not permeable to water.
  - 3. Tracheal cannula based on claim 2, characterized such that the membrane consists essentially of polytetrafluoroethylene (PTFE).
- 15 4. Tracheal cannula based on claim 2, characterized such that the membrane comprises polytetrafluoroethylene (PTFE).
  - 5. Tracheal cannula based on claim 3, characterized such that the membrane comprises a fabric made of PTFE lacing.

20

6. Tracheal cannula based on claim 4, characterized in that the membrane consists of a fabric made of FTFE lacing.

5 <sup>'</sup>

30

- 7. Tracheal cannula based on claim 1, characterized such that at the entrance of the cannula, a valve is provided which opens upon inhalation and closes upon exhalation.
- 8. Tracheal cannula based on claim 2, characterized such that at the entrance of the cannula, a valve is provided which opens upon inhalation and closes upon exhalation.
- 9. Tracheal cannula based on claim 3, characterized such that at the entrance of the cannula, a valve is provided which opens upon inhalation and closes upon exhalation.

KEIL/149/PC/US

- 5 -

15

20

Sub a3

10. Tracheal cannula based on claim 4, characterized such that at the entrance of the cannula, a valve is provided which opens upon inhalation and closes upon exhalation.

- 5 11. Tracheal cannula based on claim 5, characterized such that at the entrance of the cannula, a valve is provided which opens upon inhalation and closes upon exhalation.
- 12. Tracheal cannula based on claim 6, characterized such that at the10 entrance of the cannula, a valve is provided which opens upon inhalation and closes upon exhalation.
  - 13. Tracheal cannula based on claim 1, characterized such that the cuff is connected via a line to balloon means for the inflation of the cuff and for controlling the cuff pressure.
  - 14. Tracheal cannula based on claim 2, characterized such that the cuff is connected via a line to balloon means for the inflation of the cuff and for controlling the cuff pressure.
  - 15. Tracheal cannula based on claim 3, characterized such that the cuff is connected via a line to balloon means for the inflation of the cuff and for controlling the cuff pressure.
- 25 16. Tracheal cannula based on claim 4, characterized such that the cuff is connected via a line to balloon means for the inflation of the cuff and for controlling the cuff pressure.
- 17. Tracheal cannula based on claim 5, characterized such that the cuff is connected via a line to balloon means for the inflation of the cuff and for controlling the cuff pressure.

Su cont

- 18. Tracheal cannula based on claim 6, characterized such that the cuff is connected via a line to balloon means for the inflation of the cuff and for controlling the cuff pressure.
- 19. Tracheal cannula based on claim 7, characterized such that the cuff is connected via a line to balloon means for the inflation of the cuff and for controlling the cuff pressure.
- 20. Tracheal cannula based on claim 13, wherein said balloon means 10 comprises a pilot balloon.

adday